



A Guide to Understanding Battery Specifications

A battery is a device that converts chemical energy into electrical energy and vice versa. This summary provides an introduction to the terminology used to describe, classify, and compare batteries. It provides a basic background, defines the variables used to characterize battery operating conditions, and describes the manufacturer specifications used to characterize battery nominal and maximum characteristics.

Battery Basics

■ **Battery Classifications** – Not all batteries are created equal, even batteries of the same chemistry. The main trade-off in battery development is between power and energy: batteries can be either high-power or high-energy, but not both. Often manufacturers will classify batteries using these categories. Other common classifications are High Durability, meaning that the chemistry has been modified to provide higher battery life at the expense of power and energy.

■ **C- and E- rates** – In describing batteries, discharge current is often expressed as a C-rate in order to normalize against battery capacity, which is often very different between batteries. A C-rate is a measure of the rate at which a battery is discharged relative to its maximum capacity. A 1C rate means that the discharge current will discharge the entire battery in 1 hour. For a battery with a capacity of 100 Amp-hrs, this equates to a discharge current of 100 Amps. A 5C rate for this battery would be 500 Amps, and a C/2 rate would be 50 Amps. Similarly, an E-rate describes the discharge power. A 1E rate is the discharge power to discharge the entire battery in 1 hour.

Battery Condition

This section describes some of the variables used to describe the present condition of a battery.

■ **State of Charge (SOC)(%)** – An expression of the present battery capacity as a percentage of maximum capacity. SOC is generally calculated using current integration to determine the change in battery capacity over time.

■ **Depth of Discharge (DOD) (%)** – The percentage of battery capacity that has been discharged expressed as a percentage of maximum capacity. A discharge to at least 80 % DOD is referred to as a deep discharge.

■ **Terminal Voltage (V)** – The voltage between the battery terminals with load applied. Terminal voltage varies with SOC and discharge/charge current.

■ **Open-circuit voltage (V)** – The voltage between the battery terminals with no load applied. The open-circuit voltage depends on the battery state of charge, increasing with state of charge.

■ **Internal Resistance** – The resistance within the battery, generally different for charging and discharging, also dependent on the battery state of charge. As internal resistance increases, the battery efficiency decreases and thermal stability is reduced as more of the charging energy is converted into heat.

Battery Technical Specifications

This section explains the specifications you may see on battery technical specification sheets used to describe battery cells, modules, and packs.

■ **Nominal Voltage (V)** – The reported or reference voltage of the battery, also sometimes thought of as the “normal” voltage of the battery.

■ **Cut-off Voltage** – The minimum allowable voltage. It is this voltage that generally defines the “empty” state of the battery.

■ **Capacity or Nominal Capacity (Ah for a specific C-rate)** – The coulometric capacity, the total Amp-hours available when the battery is discharged at a certain discharge current (specified as a C-rate) from 100 percent state-of-charge to the cut-off voltage. Capacity is calculated by multiplying the discharge current (in Amps) by the discharge time (in hours) and decreases with increasing C-rate.

■ **Energy or Nominal Energy (Wh (for a specific C-rate))** – The “energy capacity” of the battery, the total Watt-hours available when the battery is discharged at a certain discharge current (specified as a C-rate) from 100 percent state-of-charge to the cut-off voltage. Energy is calculated by multiplying the discharge power (in Watts) by the discharge time (in hours). Like capacity, energy decreases with increasing C-rate.

■ **Cycle Life (number for a specific DOD)** – The number of discharge-charge cycles the battery can experience before it fails to meet specific performance criteria. Cycle life is estimated for specific charge and discharge conditions. The actual operating life of the battery is affected by the rate and depth of cycles and by other conditions such as temperature and humidity. The higher the DOD, the lower the cycle life.

■ **Charge Voltage** – The voltage that the battery is charged to when charged to full capacity. Charging schemes generally consist of a constant current charging until the battery voltage reaching the charge voltage, then constant voltage charging, allowing the charge current to taper until it is very small.

■ **Float Voltage** – The voltage at which the battery is maintained after being charge to 100 percent SOC to maintain that capacity by compensating for self-discharge of the battery.

■ **(Recommended) Charge Current** – The ideal current at which the battery is initially charged (to roughly 70 percent SOC) under constant charging scheme before transitioning into constant voltage charging.

■ **(Maximum) Internal Resistance** – The resistance within the battery, generally different for charging and discharging.